



**TECHNY
CHEMY**

TEC[®] TILE 12 LQ
Tile Grout Additive



KEY BENEFITS AND FEATURES

- Increased mechanical strength
- Provides greater adhesion to tile edges.
- Provides greater abrasion resistance.
- Increased flexural strength and flexibility.
- Enables grouts to be used where limited movement / vibration is anticipated
- Reduced water permeability
- Minimizes the risk of efflorescence.

USAGE:

- Ideal for increased performance of Tec[®] Tile 12
- Can be used both interior and exterior site conditions
- Can be used in both wet and dry conditions.

DIRECTIONS FOR USE

Application: Shake the container well before use. Add two parts of clean water to one part of Tec[®] Tile 12 LQ and blend well, add required quantity of Tec Tile 12 and grout the joints as per the instructions given in Tec Tile 12 catalogues.

PRECAUTIONS:

The working time of grout admixed with Tec Tile 12 LQ might get reduced when compared with the normal Tec Tile 12 working time in higher temperatures. Use the same mix proportion through out the application to ensure uniform color of grouts.

CLEANING :

All tools used may be cleaned with clean water

PACKING:

100 gms, 1 kg, 5 kg, 10 kg packs



Certified:

**ISO 9001 (QMS) & ISO
14001 (EMS)**



OTHER PRODUCTS

Techny manufactures lot more range of other products for construction and repair applications. They include admixtures for concrete, mortars, block making etc, waterproof and damp proof coating systems, Repair and rehabilitations products, Grouts and Anchors, Protective, Decorative and Corrosion prevention coatings, Epoxy Flooring systems, Industrial flooring systems and Tiling aids. For more details refer Separate Product brochures.

Every reasonable precaution is taken in the manufacture of the Techny products to ensure that they comply with high standards of quality. The recommendations and properties of the products are based upon what is believed to be the most reliable information available and are not intended as recommendations which infringe other patents. Although all Techny products are subject to rigid quality tests, no specific guarantee can be given, because results depend not only on quality but also on other factors beyond our control. We therefore welcome consultation in the event of doubt about application performance etc but do not accept any liability either directly or indirectly arising from the use of the products whether used as per its specifications or advice or otherwise. All transactions shall be subject to our terms of sale, delivery and payment. The leaflet supercedes the previous one and any new issue may take place without notice to supercede this edition as and when it becomes necessary.

TECHNICAL DATA SHEET
REVISED - February, 2010

CORPORATE OFFICE:

No.24, Patel Street, Ayyappa Nagar, Tiruchirapalli-620 021, Tamil Nadu, India
Phone : 0431 2458519 Fax No : 0431 2458590 Email : info@technychemistry.co.in
Web : www.technychemistry.co.in